

Technical Information Sheet



www.carolux.nl

1K PLASTIC PRIMER

Art. no. 4120

Field of application	:	For plastic parts used in de automotive industry.
Chemical basis	:	Special resins.
General qualities	:	An adhesive primer on most plastics. Do not use over Polyethylen or polystyrene.
Auxiliary materials	:	n/a
Mixing ratio (volume)	:	Ready for use. Don't add thinner.
Physical properties	:	
Density	:	0,9 kg/L
Flashpoint	:	25°C
% solids (m)	:	4%
VOC	:	800-850 g/L
Economy	:	Ca. 8m ² /L / 5 µm
Gloss	:	Matt
Substrates	:	For plastic substrates: PP Polypropylene (test always) ABS Acrylonitrile Butadiene Styrene PUR Polyurethane PC Polycarbonate PA Polyamide (nylon) EPDM Ethylene Propylene Diene Mixgpolymer Do not use on Polyethylen or Polystyrene.
Undercoats	:	Irrelevant
Finishing materials	:	Primers, Fillers Basecoats and Finishing enamels.
Cleaning the equipment	:	Uni Thinner STD 1038
Packaging	:	5 L
Colour	:	Clear
Storage life	:	Under normal storage conditions for up to two years in unopened tins.

Version 1/jan 08