

Technical Information Sheet



www.carolux.nl

UHS CLEAR COAT 80 2:1

Art. no. ZG 7250, MAT 7260

Field of application	:	For application as a clear top coat over Metallic Basecoat Series. Suitable for passenger cars.
Chemical basis	:	Ultra high solid clear acrylic finish based on high-quality hydroxy-acrylic resins.
General qualities	:	UHS Clear Coat 80 is a non-yellowing high-gloss finishing finish. Easy to use and time saving because only 1¼ spraycoats are needed to Achieve 50-70 µm coat thickness. Air-drying and force-drying.
Auxiliary materials	:	HS Hardener 60 STD 6025, Fast 6027, Extra Fast 6029 2K PU Thinner STD 1031, Fast 1032
Mixing ratio (volume)	:	2:1 (UHS Clear Coat 80 : HS Hardener 60)
Physical properties	:	
Density	:	0,98 kg/L
Flashpoint	:	21°C
Vol.% solids	:	59 %
VOC	:	420 g/L in combination with HS Hardener 60 STD
Economy	:	Ca. 12-14 m ² /L / 60 µm
Gloss	:	High gloss
Substrates	:	Solvent and waterbased Metallic Basecoats. Sanded and degreased old layers.
Finishing materials	:	Irrelevant
Cleaning the equipment	:	Uni Thinner STD 1038
Packaging	:	1 and 5 L
Colour	:	Clear
Storage life	:	Under normal storage conditions for up to two years in unopened tins.